

A large yellow seeding machine is shown in a field, with a dramatic sky featuring dark clouds and lightning in the background. The machine is a multi-row seeder, and the field appears to be a recently tilled or seeded area.

SEED STORM

BY DURAQUIP

POWER TO SOW

A STORM IS BREWING.

A new generation of seeding bars has arrived.
Australian made for Australian conditions.

SEED STORM

BY DURAQUIP

POWER TO SOW



Duraquip is an industry leader in transport and agriculture equipment, owned and operated by a WA family.

We saw a niche in the market for high quality seeding bars and decided to put our 110 years of farming experience to the task and create something that would solve grower frustrations.

Built with the same ingenuity, R&D focus and quality as the TORNADO seed fertiliser trailer, we have developed an Australian made seeding bar with the strength and flexibility required for the harshest of Australian conditions.

INTRODUCING; THE SEED STORM.



Australian Made (35-80ft options)

Built with the same ingenuity as the TORNADO seed fertiliser trailer

Solid, sleek design

Single cylinder hydraulic lift

Hardwearing greaseless Gar-Max bushes used throughout

Adjustable hydraulic pressure tines for optimum ripping in the harshest conditions

Set ripping depths with the adjustable stroke limiting valve

STRONG YET FLEXIBLE MAIN FRAME

Heavy duty axles, large hubs and bearings, Gar-Max bushes used throughout

SINGLE CYLINDER HYDRAULIC LIFT

mechanically maintains the frame level 100% of the time

FLOATING DRAWBAR

follows any contour

STREAMLINE STAINLESS STEEL AIR SYSTEM

using minimal hose for the highest efficiency

LARGE FLOATATION TYRES

20 tyres (on an 80ft frame) sit outside the main frame for maximum trash flow

OPTIONAL CASTOR LOCK SYSTEM

assists with bar tracking (patent-pending)

BIG. NOT BULKY. UNIQUE FOLDING SYSTEM FOR EASY TRANSPORT

Retracting hydraulic tines and main frame lift result in a manageable 7.5m transport width and road clearance on an 80ft bar



SEED STORM

BY DURAQUIP

POWER TO SOW



AVAILABLE MODELS: 35, 40, 45, 50, 60, 70, 80ft

EXAMPLE SPECIFICATIONS

40ft (12m)

60ft (18m)

80ft (24m)

Weight	10" spacing (250mm spacing)	~12,000Kg	~24,000Kg	~30,000Kg
	12" spacing (300mm Spacing)	~11,000Kg	~23,000Kg	~28,000Kg
Working width	10" spacing (250mm spacing)	12.19m	18.28m	24.38m
	12" spacing (300mm Spacing)			
Number of shanks	10" spacing (250mm spacing)	48	72	96
	12" spacing (300mm Spacing)	40	60	80
Transport position	Width	6.5m	7.5m	7.5m
	Height	4.3m	4.3m	5.3m
Tyres	Main Frame Wheels	500/60 - 22.5	500/60 - 22.5	500/60 - 22.5
	Wing Frame Front Castor Wheels	500/60 - 22.5	500/60 - 22.5	500/60 - 22.5
	Wing Frame Rear Wheels	500/60 - 22.5	500/60 - 22.5	500/60 - 22.5
Opener	Trip Out Force	Hydraulic- Adjustable up to ~300 kg		
	Packing Force	Spring loaded- Adjustable		
Opener to ground clearance		700mm		
Frame to ground clearance		1,000mm		
Frame depth		3,500mm		
Rank to rank spacing		1,250mm		
Number of ranks		3		
Shank to shank spacing	10" Spacing (250mm spacing)	762mm		
	12" Spacing (300mm spacing)	915mm		

Seed Storm is developed and manufactured by



www.duraquip.com.au

FOR SALES AND ENQUIRIES CONTACT YOUR LOCAL DEALER



www.mcintoshandson.com.au

Duraquip reserves the right to make changes in engineering or specifications at any time without notice. Although every effort has been made to display accurate information, no responsibility will be taken for any errors contained in this publication.